
Universal Digital Caliper MarCal 16 EWV in set



Applications

 The 16 EWV can also be used as a standard caliper (4 types of measurement).

When used in conjunction with the standard accessories; it is possible to measure recesses, grooves, etc.

In conjunction with the additional accessories; threads, bores, serrations, etc. can be measured.

Features

Functions: ON/OFF

RESET (Set display to zero) mm/inch Reference-Lock/Unlock DATA (Data transmission via connection cable) Auto-ON/OFF

- Immediate measurement due to the Reference system
- Excellent resistance against dust, coolants and lubricants, protection class IP67
- MarConnect data output, choose alternatively: USB, OPTO RS232C or Digimatic
- Dirt wipers are integrated in the slide
- Life of the battery up to 3 years
- Max measuring speed 2.5 m/s (100"/s)
- High contrast LCD with 8.5 mm high digits
- Lapped guide way

- Slide and beam made of hardened stainless steel
- Measuring blades for inside measurement
- Step measuring function
- Locking screw
- Supplied with: Case, battery, operating instructions

Technical Data


| Measuring mm (in | range* nch) | Resolution mm / inch | Error limit G mm/inch | Order no. |
|----------------------------|----------------|------------------------------|----------------------------|-------------------------|
| | (8") (8") | 0.01 /.0005" 0.01 /.0005" | 0.03/ .001" 0.03/ .001" | 4118807** 4118808*** |

^{*} in conjunction with accessories the measuring range may change

Accessories

| | | Order no. |
|--|--------|--------------------|
| Battery 3V, Type CR 2032 Data Connection Cable USB (2 m) Data Connection Cable Opto RS232C | 16 EXu | 4102520 4102357 |
| (2 m), with SUB-D jack 9-pin | 16 EXr | 4102410 |
| Data Connection Cable Digimatic (2 m), Flat plug 10-pin | 16 EXd | 4102411 |

Accessories for Data Processing see Chapter 11



^{**} includes standard accessories

^{***} excludes standard accessories

| Universal Digital Caliper MarCal 16 EWV in set | | | | | | | | | |
|--|---|-----------|-------------------|------------------|--------------------------|---------------|--|--|--|
| Standard Accessories are included in the set | | | | | | | | | |
| Catalog no. | Description | Order no. | Required quantity | | Rem | narks | | | |
| 16 Em | Depth Measuring Bridge | 4102020 | 1 | 77 75 x 7 | | | | | |
| 16 Eel | Setting Gage for inside measurement | 4118817 | 1 | 16 Eel 50 ±0,003 | | | | | |
| 16 Ec | Measuring Force Device | 4118818 | 1 | 16 Ec | | | | | |
| 16 Eea 1 | Anvils for outside measurements | 4118810 | 2 | | 16 Eea1 (%) dia. 175 | up to 5 mm | | | |
| 16 Eea 2 | Anvils for outside measurements | 4118811 | 2 | | 16 Eea2 12 5 dia. 175 | up to 5 mm | | | |
| 16 Eea 3 | Anvils for outside measurements | 4118812 | 2 | 16 Eea | 16 Eea3 | up to 5 mm | | | |
| 16 Eei 1 | Anvils for inside measurement | 4118813 | 2 | | 16 Eel1 (27) | from 7 mm | | | |
| 16 Eei 2 | Anvils for inside measurement | 4118814 | 2 | 16 Eei | 16 Eei2 12 16 Eei3 | from mm | | | |
| 16 Eei 3 | Anvils for inside measurement | 4118815 | 2 | | dia. 39 | from mm | | | |
| | Screws M2 x 8 | 4879602 | 2 | | | | | | |
| Addition | al Accessories | | | | | | | | |
| Catalog no. | Description | Order no. | Required quantity | | Rem | narks | | | |
| 16 Eei 4 | Anvils for inside measurement | 4118816 | 2 | 16 Eel4 > 08.5 | dia. 8.5 | from mm | | | |
| 16 Eab | Mounting Attachment for 844Tg/Tr and 844 Tk | 4118819 | 2 | 844 Tk 16 Eab | | | | | |
| 844 Tk | Ball Anvils | | 2 | 844 Tr/Tg | see Page 10-10 | | | | |
| 844 Tg/Tr | Thread Anvils | | 1 + 1 | 16 Eab + 10 | see Page 10-12/1 | 0-14 | | | |