


Plastic bodied limit switch Series I88

Description **I88-UV1Z AHS 270GR M16 NO**

Article number **6186335755**



| Electrical Data | | |
|---------------------------------|-----------|-----------------------------------|
| Rated insulation voltage | U_i | 250 V AC |
| Conv. thermal current | I_{the} | 10 A |
| Rated operational voltage | U_e | 240 V |
| Utilization category | | AC-15, U_e/I_e 240 V / 3 A |
| Direct opening action | \ominus | acc. to IEC/EN 60947-5-1, annex K |
| Short-circuit protective device | | Fuse 10 A gG |
| Protection class | | II, totally insulated |

| Mechanical data | |
|--------------------------|---|
| Enclosure | Thermoplastic, glass fibre reinforced (UL 94-V0) |
| Cover | Thermoplastic, glass fibre reinforced (UL 94-V0) |
| Actuator | Turret head (thermoplastic), lever (st), roller (thermoplastic) |
| Ambient air temperature | -30° C ... +80° C |
| Contact type | 1 NC, 1 NO (Zb) |
| Mechanical life | 10 x 10 ⁶ operating cycles |
| Switching frequency | ≤ 100 / min. |
| Assembly | 2 x M4 |
| Connection | 4 screw connections (M3,5) |
| Conductor cross-sections | Solid: 0,5 ... 1,5 mm ² or Litz wire with ferrules: 0,5 ... 1,5 mm ² |
| Cable entrance | 1 x tight cable gland M16x1,5 (clamp-range 5-10 mm) |
| Weight | ≈ 0,11 kg |
| Installation position | operator definable |
| Protection type | IP65 acc. to IEC/EN 60529; DIN VDE 0470 T1 |

| ID for safety engineering | |
|---------------------------|-----------------------------|
| B10d | 20 x 10 ⁶ cycles |

| Actuation | |
|--|--|
| <p>The actuating device is preferably started from 2 sides. By loosening the 4 screws the actuation assembly can be rotated in 90 degree increments such that 8 actuation directions are possible. The actuation assembly is to be again fastened to the housing using the 4 screws.</p> | |

| Standards | |
|--|--|
| VDE 0660 T100, DIN EN 60947-1, IEC 60947-1 | |
| VDE 0660 T200, DIN EN 60947-5-1, IEC 60947-5-1 | |
| DIN EN ISO 13849-1 | |

| EU Conformity | |
|------------------------------|--|
| acc. to directive 2014/35/EU | |

| Approvals | |
|---|--|
| cCSA _{US} A300 (same polarity) | |

| Notes | |
|---|--|
| <p>The degree of protection (IP code) specified applies solely to a property closed cover and the use of an equivalent cable gland with adequate cable.</p> | |