



NETLink®

NETLink® PRO PoE, PROFIBUS Ethernet Gateway

- RFC 1006 (ISO on TCP)
- CPU-to-CPU communication (with S7-300* and S7-400*)
- Support for all common S7 engineering tools
- Dynamic address assignment using DHCP
- Security functions for securing TCP/IP access
- Switchable PLC write protection
- Up to 16 TCP connections
- Up to 32 MPI/PROFIBUS connections
- Easy configuration via web interface
- Variables can be monitored in a browser window
- Support for slave configuration
- Electrical isolation for MPI/PPI/PROFIBUS
- MPI/PPI/PROFIBUS from 9.6 kbps to 12 Mbps
- For S7-200*, S7-300*, S7-400*
- Powered Device (PD) as defined in IEEE 802.3af (POE) and 802.3at (POE+)

In general, connection to each MPI/PROFIBUS terminal of the bus system or directly at the interfaces of active and passive participants is also possible. The PG socket integrated in the connector housing allows connection of additional devices. The integrated web interface offers parameterization, diagnostic, and security features, and for functional enhancements, the user can use our free diagnostic software SHTools to, for example, automatically perform firmware updates. The latest version is available for download.

It draws its supply voltage through the CPU of the automation device, or optionally via externally supplied DC 24 V, or a CAT5 network cable using a PoE power supply unit. The NETLink® PRO PoE enables the implementation of TCP/IP on the MPI/PPI/PROFIBUS with up to 32 simultaneously open connection channels. With the switchable single-master operation, passive bus participants can be addressed. The integration of SCADA, HMI, and OPC applications is possible via the widely used ISO on TCP (RFC 1006) protocol. The applications are automatically detected and forwarded by the NETLink® PRO PoE.

Technical specifications

General information	
Order number	700-881-MPI21
Article name	NETLink® PRO PoE
Scope of delivery	NETLink® PRO PoE , 3m Ethernet cable, Quick Start Guide, CD with software, and manual
Dimensions (DxWxH)	102 x 54 x 30 mm
Weight	Approx. 180 g
Communication interface	
Number	1
Type	10 Base-T 100 Base-TX
Transmission rate	10/100 Mbps autom. detection
Physical layer	Ethernet
Protocol	FDL, RFC 1006
Connection	RJ45
MPI/PPI/PROFIBUS interface	

Number	1
Type	RS485, isolated
Transmission rate	max. 12 Mbps autom. detection
Connection	SUB-D male connector, 9-pin. with PG interface and repeater
Status indicator	3 LEDs, 2 of them bi-color
Voltage supply	24 V DC, 18–30 V DC
Current draw	Max. 150 mA with DC 24 V
Ambient conditions	
Ambient temperature	0 °C ... +60 °C
Transport and storage temperature	-20 °C ... +80 °C
Relative air humidity	95 % r H without condensation
Pollution degree	2
Protection rating	IP20
Certifications	CE
CE	
RoHS	Yes
REACH	Yes