



## Technical Data Sheet

General data	
Frame size	56
Housing material	Aluminum
Install model	B14
Type of feet	Removable feet
Net weight	3.2 kg
Insulation class	F H (Standard) (Optional)
Protection degree	IP 55 IP 56 (Standard) (Optional)
Thermal protection	Without Customizable (Standard) (Optional)
Rotation direction	Clockwise Counter clockwise (Standard) (Optional)
Service duty	S1
Vibration level	A
Balance	Half-key balanced
Cable glands	1 - M16 × 1.5
Cooling	IC 411
Painting color	RAL 7024 Customizable (Standard) (Optional)
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	0.09	kW
Frequency	50	Hz
Voltage ( $\pm 5\%$ )	230 400 276 480	V Δ @ 50Hz V Y @ 50Hz V Δ @ 60Hz V Y @ 60Hz
Rotation speed	1400 1680	RPM @ 50Hz RPM @ 60Hz
Rated current	0.68 0.39	A (In) @ Δ 50Hz A (In) @ Y 50Hz
Starting current	3.1	$\times I_n$
Rated torque	0.61	Nm (Mn)
Starting torque	2.3	$\times M_n$
Breakdown torque	2.5	$\times M_n$
Efficiency	IE1 56.2 51.7 43.1	@ 100% load @ 75% load @ 50% load
Power factor cosφ	0.59	@ 100% load

Mechanical data		
Bearings brand	C&U Customizable	(Standard) (Optional)
Bearings type	6201 2RZ C3 6201 2RZ C3	(DE) (NDE)
Lifetime of bearings		20000 hours
Allowed radial load		410 N
Allowed axial load		355 N
Grease type		
Lubrication interval of NDE bearing		h
Lubrication interval of DE bearing		h
Moment of inertia	0.000240	Kg*m²
Noise level	50	dB(A)

No. 303 Kangliu Road Kangqiao Town Pudong Shanghai, 201315, China

Tel: +86 (21) 6819 2006, Fax: +86 (21) 5812 9366, Email: info@techtop.net.cn, Website: www.techtop.com